

# LL8420A

Linear Low Density Polyethylene Resin

**Special Characteristics** : InnoPlus LL8420A resin is a linear low density polyethylene which is designed for injection molding application. This grade has very narrow molecular weight distribution, offers an excellent impact strength, rigidity, environmental stress cracking resistance and processability.

**Typical Applications** : InnoPlus LL8420A is recommended for producing general purpose injection molding applications; lids, housewares, trash bins, masterbatch carrier.

## Typical Properties :

Properties	LL8420A	Unit	Test Method
<i><u>Physical Properties</u></i>			
Melt Index (190 °C, 2.16 kg)	20	g/10 min	ASTM D1238
Density	0.924	g/cm <sup>3</sup>	ASTM D792
Melting Point	123	°C	ASTM D3418
Vicat Softening Point	92	°C	ASTM D1525
<i><u>Mechanical Properties (Based on compression specimens)</u></i>			
Tensile Strength at Yield	15	MPa	ASTM D638
Tensile Strength at Break	10	MPa	ASTM D638
Elongation at Break	700	%	ASTM D638
1% Secant Modulus	310	MPa	ASTM D638
Durometer Hardness	53	Shore D	ASTM D2240

## Processing Condition :

The recommended temperature setting is in the range of 170 - 190 °C for extruder and 180 - 200 °C for Nozzle.

**Note** : Properties reported here are typical values of the product, not to be considered as specifications.

PTT Global Chemical makes no representations as to the accuracy or completeness of the information contained herein.